



SCISSOR LIFT ASSEMBLY

Product Specification



A-36, 5/16 Plate, Groove Grips

- The Attollo Lift is comprised of inner and outer rings and retaining inserts made of steel plate 5/16", ASTM A36 material.
- Retainer escutcheon plates are HRAP T-304 stainless steel, 14 gauge.
- Rubber grips are neoprene with a 60-65 Durometer Shore A. Grooved grips are designed to handle both wet and dry conditions.
- This device complies with ASME B30.20, Below-the-Hook Lifting Devices, requirements.
- Designated as Design Category A and Service Class 0 (<20,000 cycles).
- Lifting slings provided upon selection: Two (2) Nylon 1200 lb. rated, 1" single ply x 4', slings over a 3800 lb. rated oblong ring and two 3000 lb. rated shackles.

SIZE	I.D.	O.D.	WEIGHT	CAPACITY
4"	5"	7.5"	6.9 lbs.	125 lbs.
5"	6"	8.5"	7.7 lbs.	175 lbs.
6"	7"	9.5"	8.6 lbs.	175 lbs.
7"	8"	11"	11.3 lbs.	250 lbs.
8"	9"	12"	12 lbs.	250 lbs.
9"	10"	13"	12.5 lbs.	250 lbs.
10"	11"	14"	13.1 lbs.	250 lbs.
12"	13"	16.5"	20 lbs.	250 lbs.